



NEW! Expanded Assortment

Color Temperature Selectable LEDs

Introducing our innovative and versatile LEDs that offer **adjustable color temperatures**, making them the go-to choice for enhancing any environment. These multi-kelvin LEDs are designed to meet **diverse lighting needs**, ranging from warm white to daylight, creating an inviting glow for relaxation or a bright, cheerful light for productivity.

- Color-temperature-selectable LED lamps are suitable for **residential and commercial use**. Easily select between 2700K, 3000K, 3500K, 4000K, or 5000K with CCT switch.
- Omnidirectional A19s provide **even illumination** ideal for a variety of fixtures.
- Reflector LEDs deliver **task or accent lighting**, perfect for track and recessed fixtures.
- Hybrid type A/B universal T8 linear LED tubes support **multiple installation modes**: plug-and-play or direct wire for single-ended and double-ended wiring configurations.



GENERAL PURPOSE OMNI A19 LAMPS

Item No.	Energy Used (Watts)	Lamp Base	Footnotes	Domestic Code	Package Type	Equiv. Incand. Wattage	Color Designation	Finish	Color Temperature (Kelvin)	CRI	Brightness (Lumens)	Avg. Rated Hours	Life in Years*	Est. Yearly EnergyCost**	MOL
COLOR TEMPERATURE SELECTION OMNI A19															
53430	5.5	Med.	1,2	5.50MNIA19/LED/DIM/SW/27-50	Box	40	Multi 5	Soft White	2700/3000/3500/4000/5000	80	450	15000	13.6	\$0.66	4.33*
53440	9	Med.	1,2	90MNIA19/LED/DIM/SW/27-50	Box	60	Multi 5	Soft White	2700/3000/3500/4000/5000	80	800	15000	13.6	\$1.08	4.33*
53450	12	Med.	1,2	120MNIA19/LED/DIM/SW/27-50	Box	75	Multi 5	Soft White	2700/3000/3500/4000/5000	80	1100	15000	13.6	\$1.45	4.33*
53460	15	Med.	1,2	150MNIA19/LED/DIM/SW/27-50	Box	100	Multi 5	Soft White	2700/3000/3500/4000/5000	80	1600	15000	13.6	\$1.81	4.65*



53430
53440
53450



53460

*Based on 3 hrs./day

**Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on www.westinghouselighting.com.

Footnotes

1 Dimmable

2 Approved for Use in Totally Enclosed Fixtures



REFLECTOR LAMPS



Item No.	Energy Used (Watts)	Lamp Base	Footnotes	Domestic Code	Package Type	Equiv. Incand. Wattage	Color Designation	Finish	Color Temperature (Kelvin)	CRI	Brightness (Lumens)	Avg. Rated Hours	Life in Years*	Est. Yearly Energy Cost**	MOL
COLOR TEMPERATURE SELECTION REFLECTORS															
53500	6.5	Med.	1,2	6.5PAR20/LED/DIM/IndOutFL/27-50	Box	50	Multi 5	Clear	2700/3000/3500/4000/5000	90	540	25000	22.8	\$0.78	3.43"
53520	11	Med.	1,2	11PAR30/LED/DIM/IndOutFL/27-50	Box	75	Multi 5	Clear	2700/3000/3500/4000/5000	90	900	25000	22.8	\$1.32	4.57"
53510	11	Med.	1,2	11PAR30S/LED/DIM/IndOutFL/27-50	Box	75	Multi 5	Clear	2700/3000/3500/4000/5000	90	900	25000	22.8	\$1.32	3.62"
53530	15	Med.	1,2	15PAR38/LED/DIM/IndOutFL/27-50	Box	90	Multi 5	Clear	2700/3000/3500/4000/5000	80	1350	25000	22.8	\$1.81	5.31"

□ IP65 Rated

*Based on 3 hrs./day

**Based on 3 hrs./day 11¢/kWh



REFLECTOR LAMPS



Item No.	Energy Used (Watts)	Lamp Base	Footnotes	Domestic Code	Package Type	Equiv. Incand. Wattage	Color Designation	Finish	Color Temperature (Kelvin)	CRI	Brightness (Lumens)	Avg. Rated Hours	Life in Years*	Est. Yearly Energy Cost**	MOL
COLOR TEMPERATURE SELECTION REFLECTORS															
53470	6.5	Med.	1,2	6.5R20/LED/DIM/FL/27-50	Box	50	Multi 5	Frost	2700/3000/3500/4000/5000	80	525	25000	22.8	\$0.78	3.94"
53490	9	Med.	1,2	9BR30/LED/DIM/FL/27-50	Box	65	Multi 5	Frost	2700/3000/3500/4000/5000	80	750	25000	22.8	\$1.08	5.31"
53480	12.5	Med.	1	12.5BR40/LED/DIM/FL/27-50	Box	85	Multi 5	Frost	2700/3000/3500/4000/5000	80	1075	25000	22.8	\$1.51	6.46"

*Based on 3 hrs./day

**Based on 3 hrs./day 11¢/kWh



LINEAR LAMPS

All Linear LED Lamps are UL Classified and NSF Certified.



Item No.	Energy Used (Watts)	Lamp Base	Footnotes	Domestic Code	Package Type	Lamp Type Replacement	Color Designation	Finish	Color Temperature (Kelvin)	CRI	Brightness (Lumens)	Avg. Rated Hours	MOL
COLOR TEMPERATURE SELECTION T8 24, 36 AND 48 INCH SINGLE-ENDED/DOUBLE-ENDED POWERED (DesignLights Consortium® qualified product)													
Flexible installation methods: These Hybrid Type A/B Linear Lamps seamlessly replace your existing T8 fluorescent lamps with either plug-and-play compatibility or direct wire installation for single-ended and double-ended LED Tubes, offering hassle-free upgrades for various fixtures.													
53540	8	Med. BiPin	1,2	LED 8T8/24"/DIM/30-65 SE/DE AB	Sleeve	T8 & T12	Multi 5	Frost	3000/3500/4000/5000/6500	80	1130	50000	24"
53550	12	Med. BiPin	1,2	LED 12T8/36"/DIM/30-65 SE/DE AB	Sleeve	T8 & T12	Multi 5	Frost	3000/3500/4000/5000/6500	80	1700	50000	36"
53560	18	Med. BiPin	1,2	LED 18T8/48"/DIM/30-65 SE/DE AB	Sleeve	T8 & T12	Multi 5	Frost	3000/3500/4000/5000/6500	80	2250	50000	48"

◆ DLC qualified

● Dimmable when used with a compatible dimming switch. Compatible with most T8 instant start ballasts and a variety of additional T8 ballast types (see spec sheet for a complete list of compatible ballasts).

See individual product specification sheets for dimmer and ballast compatibility on www.westinghouselighting.com.

Footnotes

1 Dimmable

2 Approved for Use in Totally Enclosed Fixtures

NEW!

WESTINGHOUSE LIGHTING

For additional information or to place your order call us at 800-999-2226, or contact your Westinghouse Lighting Sales Representative.

and Westinghouse are trademarks of Westinghouse Electric Corporation. Used under license by Westinghouse Lighting. All Rights Reserved.