



# LED Lamp Program



WESTINGHOUSE LIGHTING

# LED Highlights

## NEW UPDATED TECHNOLOGY

### LED Wet Location Surface Mount Fixtures

Makira flush mount ceiling fixtures are the perfect solution for enhancing homes, offices, and any room needing overhead lighting. This line extension includes 6" black-bronze and brushed nickel finishes and a 7.5" chrome option. These multi-kelvin, color-selectable fixtures replace single kelvin fixtures, allowing you to create the perfect light appearance with just one fixture. They are wet location approved, ensuring durability and safety in areas where moisture may be present.



## PREVIOUSLY INTRODUCED

### ED37 Wattage Selectable and Soft White Filament LEDs

Introducing a new ED37 filament LED that offers three wattages in one lamp - 63/73/85 watts. It is an ideal replacement for HID lamps and corn cob lamps. You can use it in post-top lanterns, wall pack lighting, and fixtures with E39 or EX39 sockets. The LED features a 5000K color temperature, surge protection, 120-277 voltage range, and universal mounting positions.

New dimmable soft white filament LED lamps with 3000K color temperature offer beautiful illumination in various wattages. All approved for enclosed fixtures in A15 and A19 shapes for wet locations and decorative B11 for damp locations.



## PREVIOUSLY INTRODUCED

### MR16 LED and Recessed LED Downlights

The 6.5-watt GU10 base MR16 LED has a dimmable feature, a perfect fit for retail or home lighting applications. It is suitable for task or accent lighting in damp locations and can also be used for outdoor-rated accent and landscape light fixtures.

Our Slim Recessed LED Downlights have an attractive modern appearance, and are created to be installed with ease, an ideal choice for new and remodeled spaces. The latest versions of these downlights come with stepped baffle options, which include a color temperature selection switch, as well as a 3000K smooth baffle option.



Visit [www.westinghouselighting.com](http://www.westinghouselighting.com) for our complete assortment of LED lamps, light fixtures, ceiling fans and accessories.

All LED lamps in this brochure are shown unlit.

All LED lamps are approved for use in damp locations unless otherwise noted.



## DECORATIVE FILAMENT LAMPS

LAMPS SHOWN UNLIT



| Item No.               | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                    | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|------------------------|---------------------|-----------|-----------|----------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>B11 DECORATIVE</b>  |                     |           |           |                                  |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 50592                  | 2                   | Cand.     | 2,4,7     | 2B11/FilamentLED/DIM/CL/CB/27    | Box          | 25                     | Warm White        | Clear      | 2700                       | 80  | 200                 | 15000            | 13.6           | \$0.24                    | 3.82" |
| 45171                  | 3.3                 | Cand.     | 2,4,7     | 3.3B11/FilamentLED/DIM/CL/CB/27  | Box          | 40                     | Warm White        | Clear      | 2700                       | 80  | 300                 | 15000            | 13.6           | \$0.40                    | 3.82" |
| 52631                  | 3.3                 | Cand.     | 2,5,7     | 3.3B11/FilamentLED/DIM/CL/CB/30  | Box          | 40                     | Warm White        | Clear      | 3000                       | 80  | 300                 | 15000            | 13.6           | \$0.40                    | 3.82" |
| 52710                  | 4.5                 | Cand.     | 2,5,7     | 4.5B11/FilamentLED/DIM/CL/CB/27  | Box          | 60                     | Warm White        | Clear      | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.82" |
| 52651                  | 4.5                 | Cand.     | 2,5,7     | 4.5B11/FilamentLED/DIM/CL/CB/30  | Box          | 60                     | Warm White        | Clear      | 3000                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.82" |
| 53290                  | 4.5                 | Cand.     | 2,5,7     | 4.5B11/FilamentLED/DIM/SW/CB/30  | Box          | 60                     | Warm White        | Soft White | 3000                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.82" |
| 43169                  | 4.5                 | Med.      | 2,4,7     | 4.5B11/FilamentLED/DIM/CL/27     | Box          | 60                     | Warm White        | Clear      | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.58" |
| 53150                  | 4.5                 | Med.      | 2,5,7     | 4.5B11/FilamentLED/DIM/F/27      | Box          | 60                     | Warm White        | Frost      | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.54" |
| 53090                  | 6.5                 | Med.      | 2,5,7     | 6.5B11/FilamentLED/DIM/CL/27     | Box          | 100                    | Warm White        | Clear      | 2700                       | 80  | 800                 | 15000            | 13.6           | \$0.78                    | 3.54" |
| 53180                  | 6.5                 | Med.      | 2,5,7     | 6.5B11/FilamentLED/DIM/F/27      | Box          | 100                    | Warm White        | Frost      | 2700                       | 80  | 800                 | 15000            | 13.6           | \$0.78                    | 3.54" |
| <b>CA11 DECORATIVE</b> |                     |           |           |                                  |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 45172                  | 3.3                 | Cand.     | 2,4,7     | 3.3CA11/FilamentLED/DIM/CL/CB/27 | Box          | 40                     | Warm White        | Clear      | 2700                       | 80  | 300                 | 15000            | 13.6           | \$0.40                    | 4.29" |
| 52640                  | 4                   | Cand.     | 2,4,7     | 4CA11/FilamentLED/DIM/CL/CB/30   | Box          | 40                     | Warm White        | Clear      | 3000                       | 80  | 300                 | 15000            | 13.6           | \$0.48                    | 4.17" |
| 52720                  | 4.5                 | Cand.     | 2,5,7     | 4.5CA11/FilamentLED/DIM/CL/CB/27 | Box          | 60                     | Warm White        | Clear      | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 4.29" |
| 52660                  | 4.5                 | Cand.     | 2,4,7     | 4.5CA11/FilamentLED/DIM/CL/CB/30 | Box          | 60                     | Warm White        | Clear      | 3000                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 4.17" |
| <b>F15</b>             |                     |           |           |                                  |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 33193                  | 2.5                 | Med.      | 2,4,7     | 2.5F15/FilamentLED/DIM/CL/27 1CD | Card         | 25                     | Warm White        | Clear      | 2700                       | 80  | 250                 | 15000            | 13.6           | \$0.30                    | 4.33" |

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |

## FILAMENT T LAMPS

LAMPS SHOWN UNLIT



| Item No.    | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                    | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL    |
|-------------|---------------------|-----------|-----------|----------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|--------|
| <b>T6</b>   |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |        |
| 51581       | 2.5                 | Cand.     | 2,5,7     | 2.5T6/FilamentLED/DIM/CL/CB/27   | Box          | 25                     | Warm White        | Clear  | 2700                       | 80  | 250                 | 15000            | 13.6           | \$0.30                    | 3.00"  |
| 51681       | 4.5                 | Cand.     | 2,5,7     | 4.5T6/FilamentLED/DIM/CL/CB/27   | Box          | 40                     | Warm White        | Clear  | 2700                       | 80  | 450                 | 15000            | 13.6           | \$0.54                    | 3.00"  |
| <b>T6.5</b> |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |        |
| 51941       | 3.5                 | Inter.    | 2,5,7     | 3.5T6.5/FilamentLED/DIM/CL/IN/27 | Box          | 40                     | Warm White        | Clear  | 2700                       | 80  | 350                 | 15000            | 13.6           | \$0.42                    | 4.65"  |
| <b>T9</b>   |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |        |
| 45184       | 4.5                 | Med.      | 2,4,7     | 4.5T9/FilamentLED/DIM/CL/27 1CD  | Box          | 60                     | Warm White        | Clear  | 2700                       | 80  | 450                 | 15000            | 13.6           | \$0.54                    | 7.10"  |
| 45188       | 6.5                 | Med.      | 2,4,7     | 6.5T9/FilamentLED/DIM/CL/27 1CD  | Box          | 75                     | Warm White        | Clear  | 2700                       | 80  | 800                 | 15000            | 13.6           | \$0.78                    | 11.81" |
| <b>T10</b>  |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |        |
| 45185       | 3.5                 | Med.      | 2,4,7     | 3.5T10/FilamentLED/DIM/CL/27 1CD | Card         | 60                     | Warm White        | Clear  | 2700                       | 80  | 350                 | 15000            | 13.6           | \$0.42                    | 4.92"  |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

## FILAMENT ST LAMPS

LAMPS SHOWN UNLIT



| Item No.    | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                 | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|-------------|---------------------|-----------|-----------|-------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>ST15</b> |                     |           |           |                               |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 45186       | 4.5                 | Med.      | 2,4,7     | 4.5ST15/FilamentLED/DIM/CL/27 | Box          | 40                     | Warm White        | Clear  | 2700                       | 80  | 470                 | 15000            | 13.6           | \$0.54                    | 4.65" |
| 45187       | 6.5                 | Med.      | 2,4,7     | 6.5ST15/FilamentLED/DIM/CL/27 | Box          | 60                     | Warm White        | Clear  | 2700                       | 80  | 800                 | 15000            | 13.6           | \$0.78                    | 4.65" |
| <b>ST20</b> |                     |           |           |                               |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 45182       | 4.5                 | Med.      | 2,4,7     | 4.5ST20/FilamentLED/DIM/CL/27 | Box          | 40                     | Warm White        | Clear  | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 5.43" |
| 52610       | 4.5                 | Med.      | 2,4,7     | 4.5ST20/FilamentLED/DIM/CL/30 | Box          | 40                     | Warm White        | Clear  | 3000                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 5.43" |
| 53178       | 6.5                 | Med.      | 2,4,7     | 6.5ST20/FilamentLED/DIM/A/22  | Box          | 60                     | Warm White        | Amber  | 2200                       | 80  | 630                 | 15000            | 13.6           | \$0.78                    | 5.43" |
| 45183       | 6.5                 | Med.      | 2,4,7     | 6.5ST20/FilamentLED/DIM/CL/27 | Box          | 60                     | Warm White        | Clear  | 2700                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 5.43" |
| 52620       | 6.5                 | Med.      | 2,4,7     | 6.5ST20/FilamentLED/DIM/CL/30 | Box          | 60                     | Warm White        | Clear  | 3000                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 5.43" |
| 52860       | 10                  | Med.      | 2,5,7     | 10ST20/FilamentLED/DIM/CL/27  | Box          | 75                     | Warm White        | Clear  | 2700                       | 90  | 1100                | 15000            | 13.6           | \$1.20                    | 5.43" |
| 52870       | 10                  | Med.      | 2,5,7     | 10ST20/FilamentLED/DIM/CL/30  | Box          | 75                     | Warm White        | Clear  | 3000                       | 90  | 1100                | 15000            | 13.6           | \$1.20                    | 5.43" |
| 52880       | 13                  | Med.      | 2,5,7     | 13ST20/FilamentLED/DIM/CL/27  | Box          | 100                    | Warm White        | Clear  | 2700                       | 90  | 1600                | 15000            | 13.6           | \$1.57                    | 5.43" |
| 52890       | 13                  | Med.      | 2,5,7     | 13ST20/FilamentLED/DIM/CL/30  | Box          | 100                    | Warm White        | Clear  | 3000                       | 90  | 1600                | 15000            | 13.6           | \$1.57                    | 5.43" |

❖ IP40 Rated

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |

## FILAMENT LAMPS

LAMPS SHOWN UNLIT



| Item No.             | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                     | Package Type | Equiv. Incand. Wattage | Color Designation | Finish      | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|----------------------|---------------------|-----------|-----------|-----------------------------------|--------------|------------------------|-------------------|-------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>A15</b>           |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 53166                | 4.5                 | Med.      | 2,5,7     | 4.5A15/FilamentLED/DIM/CL/27      | Box          | 40                     | Warm White        | Clear       | 2700                       | 80  | 470                 | 15000            | 13.6           | \$0.54                    | 3.23* |
| 52800                | 4.5                 | Med.      | 2,5,7     | 4.5A15/FilamentLED/DIM/CL/30      | Box          | 40                     | Warm White        | Clear       | 3000                       | 80  | 470                 | 15000            | 13.6           | \$0.54                    | 3.23* |
| 52770                | 6                   | Med.      | 2,5,7     | 6A15/FilamentLED/DIM/CL/30        | Box          | 60                     | Warm White        | Clear       | 3000                       | 80  | 600                 | 15000            | 13.6           | \$0.72                    | 3.23* |
| 53250                | 6                   | Med.      | 2,5,7     | 6A15/FilamentLED/DIM/SW/30        | Box          | 60                     | Warm White        | Soft White  | 3000                       | 80  | 600                 | 15000            | 13.6           | \$0.72                    | 3.23* |
| 52780                | 8                   | Med.      | 2,5,7     | 8A15/FilamentLED/DIM/CL/30        | Box          | 75                     | Warm White        | Clear       | 3000                       | 80  | 800                 | 15000            | 13.6           | \$0.96                    | 3.23* |
| 52790                | 9                   | Med.      | 2,5,7     | 9A15/FilamentLED/DIM/CL/30        | Box          | 100                    | Warm White        | Clear       | 3000                       | 80  | 950                 | 15000            | 13.6           | \$1.08                    | 3.23* |
| <b>A19</b>           |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 53164                | 4.5                 | Med.      | 2,4,7     | 4.5A19/FilamentLED/DIM/CL/27      | Box          | 40                     | Warm White        | Clear       | 2700                       | 80  | 470                 | 15000            | 13.6           | \$0.54                    | 4.13* |
| 52570                | 4.5                 | Med.      | 2,4,7     | 4.5A19/FilamentLED/DIM/CL/30      | Box          | 40                     | Warm White        | Clear       | 3000                       | 80  | 470                 | 15000            | 13.6           | \$0.54                    | 4.13* |
| 53165                | 6.5                 | Med.      | 2,4,7     | 6.5A19/FilamentLED/DIM/CL/27      | Box          | 60                     | Warm White        | Clear       | 2700                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 4.13* |
| 51361                | 6.5                 | Med.      | 2,4,7     | 6.5A19/FilamentLED/DIM/CL/27 2PK  | Box (2)      | 60                     | Warm White        | Clear       | 2700                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 4.13* |
| 52580                | 6.5                 | Med.      | 2,4,7     | 6.5A19/FilamentLED/DIM/CL/30      | Box          | 60                     | Warm White        | Clear       | 3000                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 4.13* |
| 50163                | 6.5                 | Med.      | 2,4,7     | 6.5A19/FilamentLED/DIM/SW/27      | Box          | 60                     | Warm White        | Soft White  | 2700                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 4.13* |
| 53260                | 6.5                 | Med.      | 2,5,7     | 6.5A19/FilamentLED/DIM/SW/30      | Box          | 60                     | Warm White        | Soft White  | 3000                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 4.13* |
| 52240                | 9                   | Med.      | 2,4,7     | 9A19/FilamentLED/DIM/CL/27        | Box          | 60                     | Warm White        | Clear       | 2700                       | 80  | 800                 | 15000            | 13.6           | \$1.08                    | 4.17* |
| 51672                | 8                   | Med.      | 2,4,7     | 8A19/FilamentLED/DIM/CL/27        | Box          | 75                     | Warm White        | Clear       | 2700                       | 80  | 1100                | 15000            | 13.6           | \$0.96                    | 4.13* |
| 52590                | 8                   | Med.      | 2,4,7     | 8A19/FilamentLED/DIM/CL/30        | Box          | 75                     | Warm White        | Clear       | 3000                       | 80  | 1100                | 15000            | 13.6           | \$0.96                    | 4.13* |
| 53270                | 8                   | Med.      | 2,5,7     | 8A19/FilamentLED/DIM/SW/30        | Box          | 75                     | Warm White        | Soft White  | 3000                       | 80  | 1100                | 15000            | 13.6           | \$0.96                    | 4.13* |
| 52550                | 10                  | Med.      | 2,4,7     | 10A19/FilamentLED/DIM/CL/27       | Box          | 100                    | Warm White        | Clear       | 2700                       | 80  | 1600                | 15000            | 13.6           | \$1.20                    | 4.13* |
| 52600                | 10                  | Med.      | 2,4,7     | 10A19/FilamentLED/DIM/CL/30       | Box          | 100                    | Warm White        | Clear       | 3000                       | 80  | 1600                | 15000            | 13.6           | \$1.20                    | 4.13* |
| 53280                | 10                  | Med.      | 2,5,7     | 10A19/FilamentLED/DIM/SW/30       | Box          | 100                    | Warm White        | Soft White  | 3000                       | 80  | 1600                | 15000            | 13.6           | \$1.20                    | 4.13* |
| <b>G16.5 GLOBE</b>   |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 50242                | 4.5                 | Cand.     | 2,4,7     | 4.5G16.5/FilamentLED/DIM/CL/CB/27 | Box          | 60                     | Warm White        | Clear       | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.54                    | 3.23* |
| <b>G25 GLOBE</b>     |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 51691                | 4.5                 | Med.      | 2,4,7     | 4.5G25/FilamentLED/DIM/CH/27      | Box          | 40                     | Warm White        | Half Chrome | 2700                       | 80  | 400                 | 15000            | 13.6           | \$0.54                    | 4.72* |
| 43172                | 5.5                 | Med.      | 2,4,7     | 5.5G25/FilamentLED/DIM/CL/27      | Box          | 40                     | Warm White        | Clear       | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.66                    | 4.52* |
| 50172                | 5.5                 | Med.      | 2,4,7     | 5.5G25/FilamentLED/DIM/SW/27      | Box          | 40                     | Warm White        | Soft White  | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.66                    | 4.52* |
| <b>G25 CUT GLASS</b> |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 52680                | 5.5                 | Med.      | 2,5,7     | 5.5G25/FilamentLED/DIM/CL/CG/30   | Box          | 40                     | Warm White        | Clear       | 3000                       | 80  | 500                 | 15000            | 13.6           | \$0.66                    | 4.80* |
| <b>G40 GLOBE</b>     |                     |           |           |                                   |              |                        |                   |             |                            |     |                     |                  |                |                           |       |
| 53175                | 6.5                 | Med.      | 2,4,7     | 6.5G40/FilamentLED/DIM/CL/27      | Box          | 60                     | Warm White        | Clear       | 2700                       | 80  | 810                 | 15000            | 13.6           | \$0.78                    | 6.57* |

❖ IP40 Rated

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## DECORATIVE LAMPS

| Item No.         | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code         | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|------------------|---------------------|-----------|-----------|-----------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>FLAME TIP</b> |                     |           |           |                       |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 45124            | 4                   | Cand.     | 2,4,7     | 4C11/LED/CL/CB/27 2CD | Card (2)     | 40                     | Warm White        | Clear  | 2700                       | 80  | 300                 | 15000            | 13.6           | \$0.48                    | 4.00" |
| 45129            | 7                   | Cand.     | 2,4,7     | 7C13/LED/CL/CB/27 2CD | Card (2)     | 60                     | Warm White        | Clear  | 2700                       | 80  | 500                 | 15000            | 13.6           | \$0.84                    | 4.49" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh



## GLOWESCENT LAMPS

| Item No.   | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                     | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|------------|---------------------|-----------|-----------|-----------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>C11</b> |                     |           |           |                                   |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 52750      | 4.5                 | Cand.     | 2,4,7     | 4.5C11/GlowescentLED/DIM/CL/CB/30 | Box          | 60                     | Warm White        | Clear  | 3000                       | 80  | 480                 | 15000            | 13.6           | \$0.54                    | 4.25" |
| <b>H19</b> |                     |           |           |                                   |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 52760      | 6.5                 | Med.      | 2,4,7     | 6.5H19/GlowescentLED/DIM/CL/30    | Box          | 60                     | Warm White        | Clear  | 3000                       | 80  | 800                 | 15000            | 13.6           | \$0.78                    | 5.79" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh



## GENERAL PURPOSE LAMPS

| Item No.                      | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                 | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens)   | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|-------------------------------|---------------------|-----------|-----------|-------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|-----------------------|------------------|----------------|---------------------------|-------|
| <b>OMNI A15</b>               |                     |           |           |                               |              |                        |                   |            |                            |     |                       |                  |                |                           |       |
| 45134                         | 5                   | Med.      | 4,7       | 50MNIA15/LED/SW/27 1CD        | Card         | 40                     | Warm White        | Soft White | 2700                       | 80  | 450                   | 15000            | 13.6           | \$0.60                    | 3.54" |
| 45136                         | 5.5                 | Med.      | 4,7       | 5.50MNIA15/LED/SW/27 1CD      | Card         | 60                     | Warm White        | Soft White | 2700                       | 80  | 600                   | 15000            | 13.6           | \$0.66                    | 3.55" |
| <b>3-WAY OMNI A19 AND A21</b> |                     |           |           |                               |              |                        |                   |            |                            |     |                       |                  |                |                           |       |
| 53140                         | 3/9/12              | Med.      | 2,4,7     | 3/9/12OMNIA19/LED/3WAY/SW/27  | Box          | 30/<br>70/<br>100      | Warm White        | Soft White | 2700                       | 80  | 280/<br>950/<br>1200  | 25000            | 22.8           | \$1.45                    | 4.65" |
| 53210                         | 5/15/21             | Med.      | 4,7       | 5/15/21OMNIA21/LED/3WAY/SW/27 | Box          | 50/<br>100/<br>150     | Warm White        | Soft White | 2700                       | 80  | 600/<br>1600/<br>2150 | 25000            | 22.8           | \$2.53                    | 5.55" |
| 53220                         | 5/15/21             | Med.      | 4,7       | 5/15/21OMNIA21/LED/3WAY/SW/30 | Box          | 50/<br>100/<br>150     | Warm White        | Soft White | 3000                       | 80  | 600/<br>1600/<br>2150 | 25000            | 22.8           | \$2.53                    | 5.55" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## GENERAL PURPOSE LAMPS



OMNI A19  
MED. BASE



OMNI A19  
GU24 BASE



A19  
MED. BASE

| Item No.        | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                 | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|-----------------|---------------------|-----------|-----------|-------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>OMNI A19</b> |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 51321           | 6                   | Med.      | 2,4,7     | 60MNIA19/LED/DIM/SW/30        | Box          | 40                     | Warm White        | Soft White | 3000                       | 80  | 480                 | 25000            | 22.8           | \$0.72                    | 4.44" |
| 53189           | 6                   | Med.      | 4,7       | 60MNIA19/LED/SW/30            | Box          | 40                     | Warm White        | Soft White | 3000                       | 80  | 480                 | 15000            | 13.6           | \$0.72                    | 4.33" |
| 45138           | 6                   | Med.      | 4,7       | 60MNIA19/LED/SW/50            | Box          | 40                     | Daylight          | Soft White | 5000                       | 80  | 480                 | 15000            | 13.6           | \$0.72                    | 4.33" |
| 43697           | 9                   | Med.      | 4,7       | 90MNIA19/LED/SW/27            | Box          | 60                     | Warm White        | Soft White | 2700                       | 80  | 800                 | 25000            | 22.8           | \$1.08                    | 4.33" |
| 51840           | 9                   | Med.      | 2,4,7     | 90MNIA19/LED/DIM/SW/27        | Box          | 60                     | Warm White        | Soft White | 2700                       | 80  | 800                 | 25000            | 22.8           | \$1.08                    | 4.44" |
| 51331           | 9                   | Med.      | 2,4,7     | 90MNIA19/LED/DIM/SW/30        | Box          | 60                     | Warm White        | Soft White | 3000                       | 80  | 800                 | 25000            | 22.8           | \$1.08                    | 4.44" |
| 51341           | 9                   | Med.      | 2,4,7     | 90MNIA19/LED/DIM/SW/50        | Box          | 60                     | Daylight          | Soft White | 5000                       | 80  | 800                 | 25000            | 22.8           | \$1.08                    | 4.44" |
| 50771           | 9                   | Med.      | 2,4,7     | 90MNIA19/LED/DIM/SW/40        | Box          | 60                     | Cool White        | Soft White | 4000                       | 80  | 800                 | 25000            | 22.8           | \$1.08                    | 4.44" |
| 53127           | 9.5                 | Med.      | 4,7       | 9.50MNIA19/LED/SW/30          | Box          | 60                     | Warm White        | Soft White | 3000                       | 80  | 800                 | 15000            | 13.6           | \$1.14                    | 4.33" |
| 45160           | 9.5                 | Med.      | 4,7       | 9.50MNIA19/LED/SW/30 4PK      | Box (4)      | 60                     | Warm White        | Soft White | 3000                       | 80  | 800                 | 15000            | 13.6           | \$1.14                    | 4.33" |
| 45140           | 9.5                 | Med.      | 4,7       | 9.50MNIA19/LED/SW/50          | Box          | 60                     | Daylight          | Soft White | 5000                       | 80  | 800                 | 15000            | 13.6           | \$1.14                    | 4.33" |
| 53158           | 9.8                 | GU24      | 2,4,7     | 9.80MNIA19/LED/DIM/SW/GU24/27 | Box          | 60                     | Warm White        | Soft White | 2700                       | 80  | 800                 | 25000            | 22.8           | \$1.18                    | 4.33" |
| 53190           | 11                  | Med.      | 4,7       | 110MNIA19/LED/SW/30           | Box          | 75                     | Warm White        | Soft White | 3000                       | 80  | 1100                | 15000            | 13.6           | \$1.32                    | 4.49" |
| 50811           | 11                  | Med.      | 2,4,7     | 110MNIA19/LED/DIM/SW/30       | Box          | 75                     | Warm White        | Soft White | 3000                       | 80  | 1100                | 25000            | 22.8           | \$1.32                    | 4.33" |
| 45141           | 11                  | Med.      | 4,7       | 110MNIA19/LED/SW/50           | Box          | 75                     | Daylight          | Soft White | 5000                       | 80  | 1100                | 15000            | 13.6           | \$1.32                    | 4.49" |
| 50940           | 15                  | Med.      | 2,4,7     | 150MNIA19/LED/DIM/SW/27       | Box          | 100                    | Warm White        | Soft White | 2700                       | 80  | 1600                | 25000            | 22.8           | \$1.81                    | 4.92" |
| 51970           | 15                  | Med.      | 2,4,7     | 150MNIA19/LED/DIM/SW/30       | Box          | 100                    | Warm White        | Soft White | 3000                       | 80  | 1600                | 25000            | 22.8           | \$1.81                    | 4.92" |
| 50750           | 15                  | Med.      | 2,4,7     | 150MNIA19/LED/DIM/SW/40       | Box          | 100                    | Cool White        | Soft White | 4000                       | 80  | 1600                | 25000            | 22.8           | \$1.81                    | 4.64" |
| 50760           | 15.5                | Med.      | 4,7       | 15.50MNIA19/LED/SW/40         | Box          | 100                    | Cool White        | Soft White | 4000                       | 80  | 1600                | 15000            | 13.6           | \$1.87                    | 4.64" |
| 50790           | 15.5                | Med.      | 4,7       | 15.50MNIA19/LED/SW/50         | Box          | 100                    | Daylight          | Soft White | 5000                       | 80  | 1600                | 15000            | 13.6           | \$1.87                    | 4.64" |
| <b>A19</b>      |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 52900           | 5                   | Med.      | 4,7       | 5A19/LED/SW/27                | Box          | 40                     | Warm White        | Soft White | 2700                       | 80  | 450                 | 10000            | 9.1            | \$0.60                    | 4.17" |
| 52910           | 5                   | Med.      | 4,7       | 5A19/LED/SW/30                | Box          | 40                     | Warm White        | Soft White | 3000                       | 80  | 450                 | 10000            | 9.1            | \$0.60                    | 4.17" |
| 52920           | 5                   | Med.      | 4,7       | 5A19/LED/SW/40                | Box          | 40                     | Cool White        | Soft White | 4000                       | 80  | 450                 | 10000            | 9.1            | \$0.60                    | 4.17" |
| 52930           | 5                   | Med.      | 4,7       | 5A19/LED/SW/50                | Box          | 40                     | Daylight          | Soft White | 5000                       | 80  | 450                 | 10000            | 9.1            | \$0.60                    | 4.17" |
| 52940           | 9                   | Med.      | 4,7       | 9A19/LED/SW/27                | Box          | 60                     | Warm White        | Soft White | 2700                       | 80  | 800                 | 10000            | 9.1            | \$1.08                    | 4.17" |
| 52950           | 9                   | Med.      | 4,7       | 9A19/LED/SW/30                | Box          | 60                     | Warm White        | Soft White | 3000                       | 80  | 800                 | 10000            | 9.1            | \$1.08                    | 4.17" |
| 52960           | 9                   | Med.      | 4,7       | 9A19/LED/SW/40                | Box          | 60                     | Cool White        | Soft White | 4000                       | 80  | 800                 | 10000            | 9.1            | \$1.08                    | 4.17" |
| 52970           | 9                   | Med.      | 4,7       | 9A19/LED/SW/50                | Box          | 60                     | Daylight          | Soft White | 5000                       | 80  | 800                 | 10000            | 9.1            | \$1.08                    | 4.17" |
| 52980           | 10.5                | Med.      | 4,7       | 10.5A19/LED/SW/27             | Box          | 75                     | Warm White        | Soft White | 2700                       | 80  | 1100                | 10000            | 9.1            | \$1.26                    | 4.17" |
| 52990           | 10.5                | Med.      | 4,7       | 10.5A19/LED/SW/30             | Box          | 75                     | Warm White        | Soft White | 3000                       | 80  | 1100                | 10000            | 9.1            | \$1.26                    | 4.17" |
| 53020           | 10.5                | Med.      | 4,7       | 10.5A19/LED/SW/40             | Box          | 75                     | Cool White        | Soft White | 4000                       | 80  | 1100                | 10000            | 9.1            | \$1.26                    | 4.17" |
| 53030           | 10.5                | Med.      | 4,7       | 10.5A19/LED/SW/50             | Box          | 75                     | Daylight          | Soft White | 5000                       | 80  | 1100                | 10000            | 9.1            | \$1.26                    | 4.17" |
| 53060           | 15                  | Med.      | 4,7       | 15A19/LED/SW/27               | Box          | 100                    | Warm White        | Soft White | 2700                       | 80  | 1600                | 10000            | 9.1            | \$1.81                    | 4.57" |
| 52281           | 14                  | Med.      | 4,7       | 14A19/LED/SW/30               | Box          | 100                    | Warm White        | Soft White | 3000                       | 80  | 1500                | 15000            | 13.6           | \$1.69                    | 4.25" |
| 52301           | 14                  | Med.      | 4,7       | 14A19/LED/SW/30 2PK           | Box (2)      | 100                    | Warm White        | Soft White | 3000                       | 80  | 1500                | 15000            | 13.6           | \$1.69                    | 4.25" |
| 53080           | 15                  | Med.      | 4,7       | 15A19/LED/SW/40               | Box          | 100                    | Cool White        | Soft White | 4000                       | 80  | 1600                | 10000            | 9.1            | \$1.81                    | 4.57" |
| 52291           | 14                  | Med.      | 4,7       | 14A19/LED/SW/50               | Box          | 100                    | Daylight          | Soft White | 5000                       | 80  | 1500                | 15000            | 13.6           | \$1.69                    | 4.25" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## COLOR LAMPS

| Item No.                          | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code   | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|-----------------------------------|---------------------|-----------|-----------|-----------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>SPECIALTY - COLOR OMNI A19</b> |                     |           |           |                 |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 03153                             | 5                   | Med.      | 4,7       | 50MNIA19(LED)/R | Box          | 40                     | —                 | Red    | —                          | —   | —                   | 25000            | 22.8           | \$0.60                    | 4.33" |
| 03152                             | 6                   | Med.      | 4,7       | 60MNIA19(LED)/G | Box          | 40                     | —                 | Green  | —                          | —   | —                   | 25000            | 22.8           | \$0.72                    | 4.33" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh



## SPECIALTY 120-277V LAMPS

| Item No.        | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                 | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|-----------------|---------------------|-----------|-----------|-------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>OMNI A21</b> |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 51170           | 19                  | Med.      | 4,7       | 190MNIA21(LED)/SW/120-277V/50 | Box          | 125                    | Daylight          | Soft White | 5000                       | 80  | 2000                | 25000            | 22.8           | \$2.29                    | 5.55" |
| 51590           | 25                  | Med.      | 4,7       | 250MNIA21(LED)/SW/120-277V/30 | Box          | 150                    | Warm White        | Soft White | 3000                       | 80  | 2550                | 25000            | 22.8           | \$3.01                    | 5.47" |
| 51700           | 25                  | Med.      | 4,7       | 250MNIA21(LED)/SW/120-277V/50 | Box          | 150                    | Daylight          | Soft White | 5000                       | 80  | 2550                | 25000            | 22.8           | \$3.01                    | 5.47" |
| <b>OMNI A23</b> |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 51710           | 29                  | Med.      | 4,7       | 290MNIA23(LED)/SW/120-277V/50 | Box          | 200                    | Daylight          | Soft White | 5000                       | 80  | 3050                | 25000            | 22.8           | \$3.49                    | 6.30" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh



## GLOBE LAMPS

| Item No.           | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|--------------------|---------------------|-----------|-----------|------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>G16.5 GLOBE</b> |                     |           |           |                              |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 45131              | 7                   | Cand.     | 2,4,7     | 7G16.5(LED)/DIM/SW/CB/27 1CD | Card         | 60                     | Warm White        | Soft White | 2700                       | 80  | 500                 | 25000            | 22.8           | \$0.84                    | 2.75" |
| <b>G25 GLOBE</b>   |                     |           |           |                              |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 53011              | 6                   | Med.      | 2,4,7     | 6G25(LED)/DIM/SW/30          | Box          | 75                     | Warm White        | Soft White | 3000                       | 80  | 590                 | 25000            | 22.8           | \$0.72                    | 4.33" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## REFLECTOR LAMPS



| Item No.                        | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                 | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|---------------------------------|---------------------|-----------|-----------|-------------------------------|--------------|------------------------|-------------------|------------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>MR11 REFLECTOR</b>           |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 35153                           | 4                   | GU10      | 2,4,7     | 4MR11(LED)/DIM/FL/GU10/30 1CD | Card         | 35                     | Warm White        | White      | 3000                       | 80  | 250                 | 25000            | 22.8           | \$0.48                    | 1.89" |
| <b>MR16 REFLECTOR</b>           |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 33638                           | 4.5                 | GU5.3     | 2,4,7     | 4.5MR16(LED)/DIM/FL/30        | Hanging Box  | 35                     | Warm White        | Clear      | 3000                       | 80  | 360                 | 25000            | 22.8           | \$0.54                    | 1.85" |
| 33491                           | 6.5                 | GU5.3     | 2,4,7     | 6.5MR16(LED)/DIM/FL/30        | Hanging Box  | 50                     | Warm White        | Clear      | 3000                       | 80  | 500                 | 25000            | 22.8           | \$0.78                    | 1.85" |
| 52731                           | 6.5                 | GU10      | 2,4,7     | 6.5MR16(LED)/DIM/FL/GU10/30   | Box          | 50                     | Warm White        | White      | 3000                       | 80  | 500                 | 25000            | 22.8           | \$0.78                    | 2.17" |
| <b>R14 REFLECTOR</b>            |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 45154                           | 4                   | Inter.    | 2,4,7     | 4R14(LED)/DIM/FL/IN/27 1CD    | Card         | 25                     | Warm White        | Soft White | 2700                       | 80  | 280                 | 25000            | 22.8           | \$0.48                    | 2.55" |
| <b>R20 REFLECTOR</b>            |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 53050                           | 6.5                 | Med.      | 2,4,7     | 6.5R20(LED)/DIM/FL/27         | Box          | 50                     | Warm White        | Frost      | 2700                       | 80  | 525                 | 25000            | 22.8           | \$0.78                    | 3.93" |
| 53161                           | 6.5                 | Med.      | 2,4,7     | 6.5R20(LED)/DIM/FL/30         | Box          | 50                     | Warm White        | Frost      | 3000                       | 80  | 525                 | 25000            | 22.8           | \$0.78                    | 3.93" |
| 50110                           | 6.5                 | Med.      | 2,4,7     | 6.5R20(LED)/DIM/FL/40         | Box          | 50                     | Cool White        | Frost      | 4000                       | 80  | 525                 | 25000            | 22.8           | \$0.78                    | 3.93" |
| <b>BR30 &amp; R30 REFLECTOR</b> |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 33159                           | 8                   | GU24      | 2,4       | 8R30(LED)/DIM/FL/GU24/27      | Box          | 65                     | Warm White        | Frost      | 2700                       | 80  | 650                 | 25000            | 22.8           | \$0.96                    | 4.96" |
| 52200                           | 9                   | Med.      | 2,4,7     | 9BR30(LED)/DIM/FL/27          | Box          | 65                     | Warm White        | Frost      | 2700                       | 80  | 750                 | 25000            | 22.8           | \$1.08                    | 5.24" |
| 52210                           | 9                   | Med.      | 2,4,7     | 9BR30(LED)/DIM/FL/30          | Box          | 65                     | Warm White        | Frost      | 3000                       | 80  | 750                 | 25000            | 22.8           | \$1.08                    | 5.24" |
| 50081                           | 9                   | Med.      | 2,4,7     | 9BR30(LED)/DIM/FL/40          | Box          | 65                     | Cool White        | Frost      | 4000                       | 80  | 750                 | 25000            | 22.8           | \$1.08                    | 5.24" |
| 45148                           | 9                   | Med.      | 2,4,7     | 9BR30(LED)/DIM/FL/50          | Box          | 65                     | Daylight          | Frost      | 5000                       | 80  | 750                 | 25000            | 22.8           | \$1.08                    | 5.24" |
| <b>R40 REFLECTOR</b>            |                     |           |           |                               |              |                        |                   |            |                            |     |                     |                  |                |                           |       |
| 53064                           | 16.5                | Med.      | 2,4       | 16.5R40(LED)/DIM/FL/30        | Box          | 85                     | Warm White        | Frost      | 3000                       | 80  | 1200                | 25000            | 22.8           | \$1.99                    | 6.46" |
| 50140                           | 16.5                | Med.      | 2,4       | 16.5R40(LED)/DIM/FL/50        | Box          | 85                     | Daylight          | Frost      | 5000                       | 80  | 1200                | 25000            | 22.8           | \$1.99                    | 6.46" |

\*Based on 3 hrs./day \*\*Based on 3 hrs./day 11¢/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## REFLECTOR LAMPS

| Item No.               | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                    | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|------------------------|---------------------|-----------|-----------|----------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>PAR20 REFLECTOR</b> |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 53012                  | 7                   | Med.      | 2,5,7     | 7PAR20(LED)/DIM/IndOutFL/30      | Box          | 50                     | Warm White        | Clear  | 3000                       | 80  | 490                 | 25000            | 22.8           | \$0.84                    | 3.50" |
| 50000                  | 7                   | Med.      | 2,4,7     | 7PAR20(LED)/DIM/FL/40            | Box          | 50                     | Cool White        | Clear  | 4000                       | 80  | 490                 | 25000            | 22.8           | \$0.84                    | 3.50" |
| 50010                  | 7                   | Med.      | 2,4,7     | 7PAR20(LED)/DIM/FL/50            | Box          | 50                     | Daylight          | Clear  | 5000                       | 80  | 490                 | 25000            | 22.8           | \$0.84                    | 3.50" |
| <b>PAR30 REFLECTOR</b> |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 51800                  | 10                  | Med.      | 2,5,7     | 10PAR30S(LED)/DIM/IndOutFL/30    | Box          | 75                     | Warm White        | Clear  | 3000                       | 80  | 840                 | 25000            | 22.8           | \$1.20                    | 3.58" |
| 51450                  | 10                  | Med.      | 2,5,7     | 10PAR30(LED)/DIM/IndOutFL/30     | Box          | 75                     | Warm White        | Clear  | 3000                       | 80  | 840                 | 25000            | 22.8           | \$1.20                    | 4.57" |
| 50020                  | 10                  | Med.      | 2,4,7     | 10PAR30(LED)/DIM/FL/40           | Box          | 75                     | Cool White        | Clear  | 4000                       | 80  | 840                 | 25000            | 22.8           | \$1.20                    | 4.57" |
| <b>PAR38 REFLECTOR</b> |                     |           |           |                                  |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 53110                  | 15                  | Med.      | 2,5,7     | 15PAR38(LED)/DIM/IndOutFL/30     | Box          | 90                     | Warm White        | Clear  | 3000                       | 80  | 1350                | 25000            | 22.8           | \$1.81                    | 5.32" |
| 53114                  | 15                  | Med.      | 2,5,7     | 15PAR38(LED)/DIM/IndOutFL/30 2PK | Box (2)      | 90                     | Warm White        | Clear  | 3000                       | 80  | 1350                | 25000            | 22.8           | \$1.81                    | 5.32" |
| 50071                  | 15                  | Med.      | 2,5,7     | 15PAR38(LED)/DIM/IndOutFL/50     | Box          | 90                     | Daylight          | Clear  | 5000                       | 80  | 1350                | 25000            | 22.8           | \$1.81                    | 5.32" |

□ IP65 Rated

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh



## INDOOR/OUTDOOR COLOR REFLECTOR LAMPS



| Item No.                                 | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code     | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|------------------------------------------|---------------------|-----------|-----------|-------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|
| <b>SPECIALTY - COLOR PAR38 REFLECTOR</b> |                     |           |           |                   |              |                        |                   |        |                            |     |                     |                  |                |                           |       |
| 33147                                    | 15                  | Med.      | 5,7       | 15PAR38(LED)/FL/R | Box          | 100                    | —                 | Red    | —                          | —   | —                   | 25000            | 22.8           | \$1.81                    | 5.32" |
| 33149                                    | 15                  | Med.      | 5,7       | 15PAR38(LED)/FL/G | Box          | 100                    | —                 | Green  | —                          | —   | —                   | 25000            | 22.8           | \$1.81                    | 5.32" |
| 33151                                    | 15                  | Med.      | 5,7       | 15PAR38(LED)/FL/B | Box          | 100                    | —                 | Blue   | —                          | —   | —                   | 25000            | 22.8           | \$1.81                    | 5.32" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



BR30

## GROW LAMP

| Item No.            | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code        | Package Type | Equiv. Incand. Wattage | Color Designation | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years*                | Est. Yearly Energy Cost** | MOL   |
|---------------------|---------------------|-----------|-----------|----------------------|--------------|------------------------|-------------------|----------------------------|-----|---------------------|------------------|-------------------------------|---------------------------|-------|
| <b>BR REFLECTOR</b> |                     |           |           |                      |              |                        |                   |                            |     |                     |                  |                               |                           |       |
| 51820               | 9                   | Med.      | 4         | 9BR30(LED)/FL/GROW/G | Box          | 65                     | —                 | —                          | —   | —                   | 25000            | 22.8                          | \$1.08                    | 5.12" |
|                     |                     |           |           |                      |              |                        |                   |                            |     |                     |                  | *Based on 3 hrs./day          |                           |       |
|                     |                     |           |           |                      |              |                        |                   |                            |     |                     |                  | **Based on 3 hrs./day 11c/kWh |                           |       |

## GENERAL PURPOSE SPECIALTY LAMPS



| Item No. | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                  | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours              | Life in Years* | Est. Yearly Energy Cost** | MOL   |
|----------|---------------------|-----------|-----------|--------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|-------------------------------|----------------|---------------------------|-------|
| C7       |                     |           |           |                                |              |                        |                   |        |                            |     |                     |                               |                |                           |       |
| 52840    | 0.4                 | Cand.     | 4,7       | 0.4C7/FilamentLED/CL/CB/27 2CD | Card (2)     | 4                      | Warm White        | Clear  | 2700                       | 80  | 20                  | 15000                         | 13.6           | \$0.05                    | 2.00" |
| 52830    | 0.4                 | Cand.     | 4,7       | 0.4C7/FilamentLED/F/CB/27 2CD  | Card (2)     | 4                      | Warm White        | Frost  | 2700                       | 80  | 20                  | 15000                         | 13.6           | \$0.05                    | 2.00" |
| 52850    | 0.6                 | Cand.     | 4,7       | 0.6C7/FilamentLED/F/CB/27 2CD  | Card (2)     | 7                      | Warm White        | Frost  | 2700                       | 80  | 50                  | 15000                         | 13.6           | \$0.07                    | 2.00" |
| S11      |                     |           |           |                                |              |                        |                   |        |                            |     |                     |                               |                |                           |       |
| 55113    | 1                   | Med.      | 4,7       | 1S11/LED/CL/27 1CD             | Card         | 10                     | Warm White        | Clear  | 2700                       | 80  | 80                  | 15000                         | 13.6           | \$0.12                    | 2.05" |
| 55112    | 1                   | Med.      | 4,7       | 1S11/LED/W/27 1CD              | Card         | 10                     | Warm White        | White  | 2700                       | 80  | 80                  | 15000                         | 13.6           | \$0.12                    | 2.05" |
| 45114    | 1.5                 | Inter.    | 4,7       | 1.5S11/LED/CL/IN/27 1CD        | Card         | 10                     | Warm White        | Clear  | 2700                       | 80  | 80                  | 15000                         | 13.6           | \$0.18                    | 2.09" |
| S14      |                     |           |           |                                |              |                        |                   |        |                            |     |                     |                               |                |                           |       |
| 52810    | 1                   | Med.      | 5,7       | 1S14/FilamentLED/CL/27 1CD     | Card         | 15                     | Warm White        | Clear  | 2700                       | 80  | 120                 | 15000                         | 13.6           | \$0.12                    | 3.30" |
| 52820    | 1                   | Med.      | 5,7       | 1S14/FilamentLED/F/27 1CD      | Card         | 15                     | Warm White        | Frost  | 2700                       | 80  | 120                 | 15000                         | 13.6           | \$0.12                    | 3.30" |
| T7       |                     |           |           |                                |              |                        |                   |        |                            |     |                     |                               |                |                           |       |
| 45119    | 1.5                 | Inter.    | 4,7       | 1.5T7/LED/CL/IN/27 1CD         | Card         | 15                     | Warm White        | Clear  | 2700                       | 80  | 80                  | 15000                         | 13.6           | \$0.18                    | 2.09" |
| 33199    | 8                   | Med.      | 4,7       | 8T7/LED/F/30 1CD               | Card         | 60                     | Warm White        | Frost  | 3000                       | 80  | 800                 | 15000                         | 13.6           | \$0.96                    | 4.22" |
|          |                     |           |           |                                |              |                        |                   |        |                            |     |                     | *Based on 3 hrs./day          |                |                           |       |
|          |                     |           |           |                                |              |                        |                   |        |                            |     |                     | **Based on 3 hrs./day 11c/kWh |                |                           |       |

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |

## HALOGEN ALTERNATIVE SPECIALTY LAMP



JCD  
G9 BASE

| Item No.   | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code     | Volt | Package Type | Equiv. Halogen Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL  |
|------------|---------------------|-----------|-----------|-------------------|------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|------|
| <b>JCD</b> |                     |           |           |                   |      |              |                        |                   |        |                            |     |                     |                  |                |                           |      |
| 51641      | 5                   | G9        | 2,4,7     | 5G9/LED/DIM/CL/30 | 120  | Box          | 40                     | Warm White        | Clear  | 3000                       | 80  | 500                 | 25000            | 22.8           | \$0.60                    | 213" |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh

## PIN BASE LAMPS

Replacements for 13W, 18W, 32W, and 42W CFL pin-base lamps.



VERTICAL PL

| Item No.                                                                                  | Energy Used (Watts) | Lamp Base  | Footnotes | Domestic Code                        | Package Type | Equiv. Incand. Wattage | Color Designation | Finish     | Color Temperature (Kelvin) | CRI  | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL    |       |
|-------------------------------------------------------------------------------------------|---------------------|------------|-----------|--------------------------------------|--------------|------------------------|-------------------|------------|----------------------------|------|---------------------|------------------|----------------|---------------------------|--------|-------|
| VERTICAL INSTALLATION                                                                     |                     |            |           |                                      |              |                        |                   |            |                            |      |                     |                  |                |                           |        |       |
| 51521  | 9                   | G24Q GX24Q | 2,4,7     | 9PL/V/LED/DIM/G24Q/40 Direct Install |              | Box                    | 26                | Cool White | White                      | 4000 | 83                  | 1050             | 50000          | 45.6                      | \$1.08 | 4.65" |

Dimmable when used with a compatible dimming ballast.

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh

\* Lumen output is based on ballast type.

♦ DLC qualified

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## SLIM RECESSED DOWNLIGHTS

| Item No.                                                       | Energy Used (Watts) | Footnotes | Domestic Code                          | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   | MOD   |
|----------------------------------------------------------------|---------------------|-----------|----------------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|-------|
| <b>ROUND SLIM WITH COLOR TEMPERATURE SELECTION</b>             |                     |           |                                        |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 52161 ♦ ●                                                   | 8                   | 2,5       | 8R/3"LED/DIM/WH/SUM/FL/27-50           | Box          | 45                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 480                 | 50000            | 45.6           | \$0.96                    | 1.00" | 3.74" |
| 52012 ★ ♦ ■                                                    | 10                  | 2,5       | 10R/4"LED/DIM/SLIM/FL/27-50            | Box          | 65                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 80  | 650                 | 50000            | 45.6           | \$1.20                    | 1.02" | 5.04" |
| 52050 ▲ ♦ ●                                                    | 11                  | 2,5       | 11R/5"LED/DIM/SLIM/FL/27-50            | Box          | 75                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 80  | 800                 | 50000            | 45.6           | \$1.32                    | 1.02" | 6.29" |
| 52022 ♦ ♦ ■                                                    | 12                  | 2,5       | 12R/6"LED/DIM/SLIM/FL/27-50            | Box          | 80                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 80  | 950                 | 50000            | 45.6           | \$1.45                    | 1.02" | 7.17" |
| 52450 ♦ ♦                                                      | 18                  | 2,5       | 18R/8"LED/DIM/WH/SUM/FL/120-277V/27-50 | Box          | 100                    | Multi 5           | White  | 2700/3000/3500/4000/5000   | 80  | 1600                | 50000            | 45.6           | \$2.17                    | 1.02" | 9.29" |
| <b>ROUND SLIM STEP BAFFLE WITH COLOR TEMPERATURE SELECTION</b> |                     |           |                                        |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 52261 ★ ♦ ■                                                 | 10                  | 2,5       | 10R/4"LED/DIM/SLIMBAFFLE/FL/27-50      | Box          | 65                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 650                 | 50000            | 45.6           | \$1.20                    | 1.42" | 5.08" |
| 24 52271 ♦ ♦ ■                                                 | 12                  | 2,5       | 12R/6"LED/DIM/SLIMBAFFLE/FL/27-50      | Box          | 80                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 900                 | 50000            | 45.6           | \$1.45                    | 1.42" | 7.17" |
| <b>ROUND DEEP STEP BAFFLE WITH COLOR TEMPERATURE SELECTION</b> |                     |           |                                        |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 52370 ★ ♦ ■                                                 | 12                  | 2,5       | 12R/4"LED/DIM/DEEPBAFFLE/FL/27-50      | Box          | 65                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 750                 | 50000            | 45.6           | \$1.45                    | 1.74" | 5.09" |
| 24 52380 ♦ ♦                                                   | 15                  | 2,5       | 15R/6"LED/DIM/DEEPBAFFLE/FL/27-50      | Box          | 100                    | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 1000                | 50000            | 45.6           | \$1.81                    | 1.86" | 7.32" |
| <b>FIRE-RATED ROUND SLIM WITH COLOR TEMPERATURE SELECTION</b>  |                     |           |                                        |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 53100 ★ ♦ ■                                                 | 11                  | 2,5       | 11R/4"LED/DIM/SLIM/FR/FL/27-50         | Box          | 80                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 900                 | 50000            | 45.6           | \$1.32                    | 2.32" | 5.04" |
| 24 53120 ★ ♦ ■                                                 | 12                  | 2,5       | 15R/6"LED/DIM/SLIM/FR/FL/27-50         | Box          | 100                    | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 1230                | 50000            | 45.6           | \$1.81                    | 2.32" | 7.17" |
| <b>ROUND SLIM</b>                                              |                     |           |                                        |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 52180                                                          | 7                   | 2,4       | 7R/3"LED/DIM/WH/SLIM/FL/40             | Box          | 40                     | Cool White        | White  | 4000                       | 80  | 450                 | 50000            | 45.6           | \$0.84                    | 0.98" | 3.35" |
| 52190                                                          | 7                   | 2,4       | 7R/3"LED/DIM/WH/SLIM/FL/50             | Box          | 40                     | Daylight          | White  | 5000                       | 80  | 450                 | 50000            | 45.6           | \$0.84                    | 0.98" | 3.35" |
| 24 50951 ★ ♦ ♦ ■                                               | 10                  | 2,5       | 10R/4"LED/DIM/WH/SLIM/FL/27            | Box          | 65                     | Warm White        | White  | 2700                       | 90  | 650                 | 50000            | 45.6           | \$1.20                    | 1.02" | 5.04" |
| 24 50971 ★ ♦ ♦ ■                                               | 10                  | 2,5       | 10R/4"LED/DIM/WH/SLIM/FL/30            | Box          | 65                     | Warm White        | White  | 3000                       | 90  | 650                 | 50000            | 45.6           | \$1.20                    | 1.02" | 5.04" |
| 24 51072 ♦ ♦ ♦ ■                                               | 12                  | 2,5       | 12R/6"LED/DIM/WH/SLIM/FL/30            | Box          | 80                     | Warm White        | White  | 3000                       | 90  | 900                 | 50000            | 45.6           | \$1.45                    | 1.02" | 7.17" |

★ Compatible with item #509506913

▲ Compatible with item #520506913

♦ Compatible with item #510306913

\*Based on 3 hrs./day \*\*Based on 3 hrs./day 11c/kWh

♦ Compatible with Special Order accessory item #509516931

♦ IP40 Rated

■ Compatible with item #509516913

● Compatible with item #520516913

24 Can be used to comply with the 2022 Title 24, part 6, high efficacy light source requirements.

## SLIM RECESSED DOWNLIGHT ACCESSORIES



| Item No.    | Footnotes | Description                                                    | Height | Width  | Depth |
|-------------|-----------|----------------------------------------------------------------|--------|--------|-------|
| 509516931 * |           | 10 ft. Extension Cord for Slim Recessed Downlights             | —      | —      | —     |
| 509506913   |           | Bracket for 4 in. Slim Recessed Downlights                     | 0.03"  | 26.00" | 6.25" |
| 520506913   |           | Bracket for 5 in. Slim Recessed Downlights                     | 0.03"  | 26.00" | 8.35" |
| 510306913   |           | Bracket for 6 in. Slim Recessed Downlights                     | 0.03"  | 26.00" | 8.38" |
| 509516913   |           | 4 in. & 6 in. Combination Bracket for Slim Recessed Downlights | 0.03"  | 26.00" | 8.30" |
| 520516913   |           | 3 in. & 5 in. Combination Bracket for Slim Recessed Downlights | 0.03"  | 26.00" | 8.30" |

\* SPECIAL ORDER ITEM - CALL YOUR WESTINGHOUSE LIGHTING REPRESENTATIVE FOR ADDITIONAL INFORMATION

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

1 New Item  
2 Dimmable

3 Low Voltage (12V)  
4 Approved for Damp Location

5 Approved for Wet Location  
6 Indoor Application Only

7 Approved for Use in Totally Enclosed Fixtures



## RECESSED DOWNLIGHTS

All Recessed LED Downlight Kits are UL or ETL Classified.

| Item No.                                              | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   | MOD   |
|-------------------------------------------------------|---------------------|-----------|-----------|------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|-------|
| <b>SMOOTH BAFFLE WITH COLOR TEMPERATURE SELECTION</b> |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 52430 ❖                                            | 10                  | Med.      | 2,5       | 10R/4"/LED/DIM/FL/27-50      | Box          | 65                     | Multi 5           | Frost  | 2700/3000/3500/4000/5000   | 90  | 750                 | 50000            | 45.6           | \$1.20                    | 2.99" | 5.08" |
| 24 52440 ❖                                            | 14                  | Med.      | 2,5       | 14R/5-6"/LED/DIM/FL/27-50    | Box          | 100                    | Multi 5           | Frost  | 2700/3000/3500/4000/5000   | 90  | 1100                | 50000            | 45.6           | \$1.69                    | 3.22" | 7.36" |
| <b>STEP BAFFLE WITH COLOR TEMPERATURE SELECTION</b>   |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 51401                                              | 6.5                 | Med.      | 2,5       | 6.5R/4"/LED/DIM/FL/27-50     | Box          | 65                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 550                 | 50000            | 45.6           | \$0.78                    | 2.48" | 5.27" |
| 24 52350                                              | 10                  | Med.      | 2,5       | 10R/4"/LED/DIM/FL/27-50      | Box          | 65                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 750                 | 50000            | 45.6           | \$1.20                    | 3.11" | 5.09" |
| 24 51411                                              | 11                  | Med.      | 2,5       | 11R/5-6"/LED/DIM/FL/27-50    | Box          | 80                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 1000                | 50000            | 45.6           | \$1.32                    | 2.87" | 7.48" |
| 24 52360                                              | 14                  | Med.      | 2,5       | 14R/5-6"/LED/DIM/FL/27-50    | Box          | 100                    | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 1100                | 50000            | 45.6           | \$1.69                    | 3.23" | 7.32" |
| <b>STEP BAFFLE</b>                                    |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 51047                                                 | 10                  | Med.      | 2,5       | 10R/4"/LED/DIM/FL/30         | Box          | 65                     | Warm White        | Frost  | 3000                       | 90  | 670                 | 50000            | 45.6           | \$1.20                    | 2.88" | 5.52" |
| 24 52390                                              | 12                  | Med.      | 2,5       | 12R/5-6"/LED/DIM/FL/30       | Box          | 80                     | Warm White        | Frost  | 3000                       | 90  | 850                 | 50000            | 45.6           | \$1.45                    | 2.91" | 7.24" |
| <b>SMOOTH BAFFLE</b>                                  |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 41041                                                 | 8                   | Med.      | 2,4       | 8R/4"/LED/DIM/FL/30          | Box          | 65                     | Warm White        | Frost  | 3000                       | 80  | 650                 | 50000            | 45.6           | \$0.96                    | 3.50" | 5.04" |
| 41040                                                 | 14                  | Med.      | 2,4       | 14R/5"/LED/DIM/FL/27         | Box          | 80                     | Warm White        | Frost  | 2700                       | 80  | 1000                | 50000            | 45.6           | \$1.69                    | 3.54" | 6.30" |
| <b>SQUARE STEP BAFFLE</b>                             |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 24 52460 ❖                                            | 11                  | Med.      | 2,5       | 11R/4"/LED/DIM/SQ/FL/27-50   | Box          | 65                     | Multi 5           | Frost  | 2700/3000/3500/4000/5000   | 90  | 750                 | 50000            | 45.6           | \$1.32                    | 3.24" | 5.00" |
| 24 52470 ❖                                            | 14                  | Med.      | 2,5       | 14R/5-6"/LED/DIM/SQ/FL/27-50 | Box          | 100                    | Multi 5           | Frost  | 2700/3000/3500/4000/5000   | 90  | 1100                | 50000            | 45.6           | \$1.69                    | 3.54" | 6.77" |
| <b>SLOPED STEP BAFFLE</b>                             |                     |           |           |                              |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 50820                                                 | 10                  | Med.      | 2,4       | 10R/4"/LED/DIM/SLP/FL/27     | Box          | 65                     | Warm White        | Frost  | 2700                       | 90  | 650                 | 35000            | 31.9           | \$1.20                    | 3.35" | 5.15" |
| 50830                                                 | 10                  | Med.      | 2,4       | 10R/4"/LED/DIM/SLP/FL/30     | Box          | 65                     | Warm White        | Frost  | 3000                       | 90  | 650                 | 35000            | 31.9           | \$1.20                    | 3.35" | 5.15" |
| 50840                                                 | 13                  | Med.      | 2,4       | 13R/6"/LED/DIM/SLP/FL/27     | Box          | 80                     | Warm White        | Frost  | 2700                       | 90  | 900                 | 35000            | 31.9           | \$1.57                    | 3.50" | 7.28" |
| 50850                                                 | 13                  | Med.      | 2,4       | 13R/6"/LED/DIM/SLP/FL/30     | Box          | 80                     | Warm White        | Frost  | 3000                       | 90  | 900                 | 35000            | 31.9           | \$1.57                    | 3.50" | 7.28" |

❖ IP40 Rated

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11c/kWh

24 Can be used to comply with the 2022 Title 24, part 6, high efficacy light source requirements.

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- 1 New Item
- 2 Dimmable

- 3 Low Voltage (12V)
- 4 Approved for Damp Location

- 5 Approved for Wet Location
- 6 Indoor Application Only

- 7 Approved for Use in Totally Enclosed Fixtures





## GIMBAL RECESSED DOWNLIGHTS

All Gimbal Recessed LED Downlights are ETL Listed.



| Item No.                   | Energy Used (Watts) | Footnotes | Domestic Code                  | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL   | MOD   |
|----------------------------|---------------------|-----------|--------------------------------|--------------|------------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|----------------|---------------------------|-------|-------|
| GIMBAL RECESSED DOWNLIGHTS |                     |           |                                |              |                        |                   |        |                            |     |                     |                  |                |                           |       |       |
| 52121                      | 7                   | 2,5       | 7R/3"/LED/DIM/WH/GIMBAL/27-50  | Box          | 45                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 550                 | 50000            | 45.6           | \$084                     | 1.21" | 3.76" |
| 52141                      | 12                  | 2,5       | 12R/4"/LED/DIM/WH/GIMBAL/27-50 | Box          | 80                     | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 850                 | 50000            | 45.6           | \$1.45                    | 1.38" | 5.04" |
| 52560                      | 15                  | 2,5       | 15R/6"/LED/DIM/WH/GIMBAL/27-50 | Box          | 100                    | Multi 5           | White  | 2700/3000/3500/4000/5000   | 90  | 1100                | 50000            | 45.6           | \$1.81                    | 2.00" | 7.21" |

⬢ Compatible with Bracket for 4 in. Slim Recessed Downlights sold separately (Item# 509506913)

⬢ IP40 Rated

■ Compatible with item #509516913

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh

Can be used to comply with the 2022 Title 24, part 6, high efficacy light source requirements.

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

1 New Item  
2 Dimmable

3 Low Voltage (12V)  
4 Approved for Damp Location

5 Approved for Wet Location  
6 Indoor Application Only

7 Approved for Use in Totally Enclosed Fixtures



51190

## SHOEBOX LAMP

This Shoebox LED Lamp is 100-277V.

| Item No.     | Energy Used (Watts) | Lamp Base            | Footnotes | Domestic Code    | Package Type | Equiv. HID Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | MOL   |
|--------------|---------------------|----------------------|-----------|------------------|--------------|--------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|-------|
| SHOEBOX LAMP |                     |                      |           |                  |              |                    |                   |        |                            |     |                     |                  |       |
| 51190        | 80                  | Mogul/Extended Mogul | 4,7       | 80SB(LED)EX39/50 | Box          | 250                | Daylight          | Clear  | 5000                       | 80  | 9200                | 50000            | 8.70" |

See product specification sheet for minimum compartment dimensions.

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## FILAMENT HIGH-LUMEN

These LED Lamps are 120-277V.



| Item No.               | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code                                   | Package Type | Equiv. Incand. Wattage | Equiv. CFL Wattage | Equiv. HID Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | MOL    |
|------------------------|---------------------|-----------|-----------|-------------------------------------------------|--------------|------------------------|--------------------|--------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|--------|
| <b>ED23.5 FILAMENT</b> |                     |           |           |                                                 |              |                        |                    |                    |                   |        |                            |     |                     |                  |        |
| 52480                  | 14                  | Med.      | 5,7       | 14ED23.5/FilamentLED/CL/120-277V/E26/2150       | Box          | 125                    | 55                 | 50                 | -                 | Clear  | 2150                       | 80  | 1750                | 25000            | 7.09"  |
| 52500                  | 14                  | Med.      | 5,7       | 14ED23.5/FilamentLED/CL/120-277V/E26/50         | Box          | 125                    | 55                 | 50                 | Daylight          | Clear  | 5000                       | 80  | 2000                | 25000            | 7.09"  |
| 52510                  | 19                  | Med.      | 5,7       | 19ED23.5/FilamentLED/CL/120-277V/E26/50         | Box          | 150                    | 60                 | 100                | Daylight          | Clear  | 5000                       | 80  | 3000                | 25000            | 7.09"  |
| 52520                  | 28                  | Med.      | 5,7       | 28ED23.5/FilamentLED/CL/120-277V/E26/50         | Box          | 200                    | 65                 | 150                | Daylight          | Clear  | 5000                       | 80  | 4000                | 25000            | 7.60"  |
| <b>ED28 FILAMENT</b>   |                     |           |           |                                                 |              |                        |                    |                    |                   |        |                            |     |                     |                  |        |
| 52490                  | 32                  | Med.      | 5,7       | 32ED28/FilamentLED/CL/120-277V/E26/2150         | Box          | 300                    | 85                 | 175                | -                 | Clear  | 2150                       | 80  | 4500                | 25000            | 9.53"  |
| 52530                  | 32                  | Med.      | 5,7       | 32ED28/FilamentLED/CL/120-277V/E26/50           | Box          | 300                    | 85                 | 175                | Daylight          | Clear  | 5000                       | 80  | 5000                | 25000            | 9.53"  |
| 52251                  | 32                  | EX39      | 5,7       | 32ED28/FilamentLED/CL/120-277V/EX39/50          | Box          | 300                    | 85                 | 175                | Daylight          | Clear  | 5000                       | 80  | 5000                | 25000            | 8.46"  |
| 52540                  | 36                  | Med.      | 5,7       | 36ED28/FilamentLED/CL/120-277V/E26/50           | Box          | 400                    | 105                | 200                | Daylight          | Clear  | 5000                       | 80  | 6000                | 25000            | 9.53"  |
| 52341                  | 36                  | Mogul     | 5,7       | 36ED28/FilamentLED/CL/120-277V/E39/50           | Box          | 400                    | 105                | 200                | Daylight          | Clear  | 5000                       | 80  | 6000                | 25000            | 8.46"  |
| 52421                  | 45                  | Mogul     | 5,7       | 45ED28/FilamentLED/CL/120-277V/E39/50           | Box          | 500                    | 125                | 250                | Daylight          | Clear  | 5000                       | 80  | 7500                | 25000            | 9.06"  |
| <b>ED32 FILAMENT</b>   |                     |           |           |                                                 |              |                        |                    |                    |                   |        |                            |     |                     |                  |        |
| 52690♦                 | 54                  | EX39      | 5,7       | 54ED32/FilamentLED/CL/120-277V/EX39/50          | Box          | 650                    | 135                | 320                | Daylight          | Clear  | 5000                       | 80  | 10000               | 50000            | 9.45"  |
| <b>ED37 FILAMENT</b>   |                     |           |           |                                                 |              |                        |                    |                    |                   |        |                            |     |                     |                  |        |
| 52670                  | 65                  | EX39      | 5,7       | 65ED37/FilamentLED/CL/120-277V/EX39/50          | Box          | 750                    | 150                | 400                | Daylight          | Clear  | 5000                       | 80  | 12000               | 25000            | 11.50" |
| 53240♦                 | 63/73/85            | EX39      | 5,7       | 63/73/85ED37/FilamentLED/WS/CL/120-277V/EX39/50 | Box          | 750/800/850            | 150/175/200        | 400/420/450        | Daylight          | Clear  | 5000                       | 80  | 12000/14000/16500   | 50000            | 11.50" |

♦ DLC qualified



## HIGH-LUMEN LAMPS

All High-Lumen LED Lamps are 120-277V.



| Item No.          | Energy Used (Watts) | Lamp Base | Footnotes | Domestic Code        | Package Type | Equiv. Incand. Wattage | Color Designation | Finish | Color Temperature (Kelvin) | CRI   | Brightness (Lumens) | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** | MOL    |
|-------------------|---------------------|-----------|-----------|----------------------|--------------|------------------------|-------------------|--------|----------------------------|-------|---------------------|------------------|----------------|---------------------------|--------|
| <b>HIGH LUMEN</b> |                     |           |           |                      |              |                        |                   |        |                            |       |                     |                  |                |                           |        |
| 35165             | 22                  | Med.      | 4,7       | 22T19/LED/HL/50      | Box          | 150                    | 55                | 100    | Daylight                   | Clear | 5000                | 80               | 2860           | 50000                     | 7.09"  |
| 35162             | 36                  | Med.      | 4,7       | 36T30/LED/HL/50      | Box          | 200                    | 65                | 150    | Daylight                   | Clear | 5000                | 80               | 4680           | 50000                     | 8.27"  |
| 35164♦            | 45                  | Mogul     | 4,7       | 45T30/LED/HL/E39/50  | Box          | 300                    | 85                | 175    | Daylight                   | Clear | 5000                | 80               | 5850           | 50000                     | 9.25"  |
| 35166♦            | 54                  | Mogul     | 4,7       | 54T30/LED/HL/E39/50  | Box          | 400                    | 105               | 250    | Daylight                   | Clear | 5000                | 80               | 7020           | 50000                     | 10.24" |
| 45167♦            | 100                 | Mogul     | 4,7       | 100T38/LED/HL/E39/50 | Box          | 750                    | 150               | 400    | Daylight                   | Clear | 5000                | 80               | 15000          | 50000                     | 11.10" |
| 35180♦            | 120                 | Mogul     | 4,7       | 120T38/LED/HL/E39/50 | Box          | 1000                   | 250               | 800    | Daylight                   | Clear | 5000                | 80               | 18000          | 50000                     | 13.46" |

♦ DLC qualified

See product specification sheet for minimum compartment dimensions.

See product specification sheet for minimum compartment dimensions.

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- |            |                              |                             |                                                 |
|------------|------------------------------|-----------------------------|-------------------------------------------------|
| 1 New Item | 3 Low Voltage (12V)          | 5 Approved for Wet Location | 7 Approved for Use in Totally Enclosed Fixtures |
| 2 Dimmable | 4 Approved for Damp Location | 6 Indoor Application Only   |                                                 |



## LINEAR LAMPS

All Linear LED Lamps are  
UL Classified and NSF Certified.



| Item No.                                                                                         | Energy Used (Watts) | Lamp Base  | Footnotes | Domestic Code                            | Package Type | Lamp Type Replacement | Color Designation | Finish | Color Temperature (Kelvin) | CRI | Brightness (Lumens) | Avg. Rated Hours | MOL |
|--------------------------------------------------------------------------------------------------|---------------------|------------|-----------|------------------------------------------|--------------|-----------------------|-------------------|--------|----------------------------|-----|---------------------|------------------|-----|
| <b>T5 46 INCH</b>                                                                                |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 53788                                                                                            | 25                  | Mini BiPin | 4         | LED 25T5/46"/DIM/40 Direct Install       | Sleeve       | T5                    | Cool White        | Frost  | 4000                       | 82  | 3500                | 50000            | 46" |
| <b>T8 24 INCH (DesignLights Consortium® qualified product)</b>                                   |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 50260                                                                                            | 9                   | Med. BiPin | 4,7       | LED 9T8/24"/DIM/40 Ballast Bypass        | Sleeve       | T8 & T12              | Cool White        | Frost  | 4000                       | 82  | 1150                | 50000            | 24" |
| <b>T8 36 INCH (DesignLights Consortium® qualified product)</b>                                   |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 50280                                                                                            | 12                  | Med. BiPin | 4,7       | LED 12T8/36"/DIM/40 Ballast Bypass       | Sleeve       | T8 & T12              | Cool White        | Frost  | 4000                       | 82  | 1450                | 50000            | 36" |
| <b>T8 48 INCH (DesignLights Consortium® qualified product)</b>                                   |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 53852                                                                                            | 11                  | Med. BiPin | 4,7       | LED 11T8/48"/DIM/50 Direct Install       | Sleeve       | T8                    | Daylight          | Frost  | 5000                       | 82  | 1800                | 50000            | 48" |
| 52320                                                                                            | 14                  | Med. BiPin | 4,7       | LED 14T8/48"/DIM/40 Direct Install       | Sleeve       | T8                    | Cool White        | Frost  | 4000                       | 82  | 2200                | 50000            | 48" |
| 52330                                                                                            | 14                  | Med. BiPin | 4,7       | LED 14T8/48"/DIM/50 Direct Install       | Sleeve       | T8                    | Daylight          | Frost  | 5000                       | 82  | 2200                | 50000            | 48" |
| <b>T8 48 INCH SINGLE-ENDED/DOUBLE-ENDED POWERED (DesignLights Consortium® qualified product)</b> |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 51561                                                                                            | 14                  | Med. BiPin | 4,7       | LED 14T8/48"/DIM/40 SE/DE Ballast Bypass | Sleeve       | T8 & T12              | Cool White        | Frost  | 4000                       | 83  | 1800                | 50000            | 48" |
| 51571                                                                                            | 14                  | Med. BiPin | 4,7       | LED 14T8/48"/DIM/50 SE/DE Ballast Bypass | Sleeve       | T8 & T12              | Daylight          | Frost  | 5000                       | 83  | 1800                | 50000            | 48" |
| 51421                                                                                            | 17                  | Med. BiPin | 4,7       | LED 17T8/48"/DIM/35 SE/DE Ballast Bypass | Sleeve       | T8 & T12              | Cool White        | Frost  | 3500                       | 83  | 2100                | 50000            | 48" |
| 51431                                                                                            | 17                  | Med. BiPin | 4,7       | LED 17T8/48"/DIM/40 SE/DE Ballast Bypass | Sleeve       | T8 & T12              | Cool White        | Frost  | 4000                       | 83  | 2200                | 50000            | 48" |
| 51441                                                                                            | 17                  | Med. BiPin | 4,7       | LED 17T8/48"/DIM/50 SE/DE Ballast Bypass | Sleeve       | T8 & T12              | Daylight          | Frost  | 5000                       | 83  | 2200                | 50000            | 48" |
| <b>T8 96 INCH (DesignLights Consortium® qualified product)</b>                                   |                     |            |           |                                          |              |                       |                   |        |                            |     |                     |                  |     |
| 34051                                                                                            | 40                  | Single Pin | 4,7       | LED 40T8/96"/DIM/40 Ballast Bypass       | Bulk         | T8 & T12              | Cool White        | Frost  | 4000                       | 82  | 5500                | 50000            | 96" |
| 34052                                                                                            | 40                  | Single Pin | 4,7       | LED 40T8/96"/DIM/50 Ballast Bypass       | Bulk         | T8 & T12              | Daylight          | Frost  | 5000                       | 82  | 5500                | 50000            | 96" |

- ◆ DLC qualified
- Replace F54T5HO linear fluorescent lamps.
- ◐ Dimmable when used with a compatible dimming ballast.
- ⊗ Dimmable when used in conjunction with a (0-10V) dimming system and dimming module sold separately (Item# 502606930).
- Ballast Bypass lamps are designed to operate on voltages ranging from 120-277V.

## T8 LED BALLAST BYPASS LAMP DIMMER MODULE



502606930

| Item No.  | Footnotes | Description                              | Height | Width  | Depth |
|-----------|-----------|------------------------------------------|--------|--------|-------|
| 502606930 |           | T8 LED Ballast Bypass Lamp Dimmer Module | 1.20"  | 12.68" | 1.70" |

See individual product specification sheets for dimmer and ballast compatibility on [www.westinghouselighting.com](http://www.westinghouselighting.com).

### Footnotes

- 1 New Item
- 2 Dimmable
- 3 Low Voltage (12V)
- 4 Approved for Damp Location
- 5 Approved for Wet Location
- 6 Indoor Application Only
- 7 Approved for Use in Totally Enclosed Fixtures

**6" LED Surface Mount**  
Height: 1" Diameter: 6"



61337  
White Finish  
with Frosted Lens



61338  
Black-Bronze Finish  
with Frosted Lens



61339  
Brushed Nickel Finish  
with Frosted Lens

**7.5" LED Surface Mount**  
Height: 1.25" Diameter: 7.50"



61340  
White Finish  
with Frosted Lens



61341  
Black-Bronze Finish  
with Frosted Lens



61342  
Brushed Nickel Finish  
with Frosted Lens



61343  
Chrome Finish  
with Frosted Lens



**LED SURFACE  
MOUNT FIXTURES**

| Item No.                           | Energy Used (Watts) | Equiv. Incand. Wattage | Finish         | Color Designation | Color Temperature (Kelvin)  | Brightness (Lumens) | CRI | Avg. Rated Hours | Life in Years* | Est. Yearly Energy Cost** |
|------------------------------------|---------------------|------------------------|----------------|-------------------|-----------------------------|---------------------|-----|------------------|----------------|---------------------------|
| <b>6 INCH LED SURFACE MOUNTS</b>   |                     |                        |                |                   |                             |                     |     |                  |                |                           |
| 24 61337                           | 11                  | 60                     | White          | Multi 5           | 2700/3000<br>3500/4000/5000 | 840                 | 90  | 50000            | 45.6           | \$1.32                    |
| 24 61338                           | 11                  | 60                     | Black-Bronze   | Multi 5           | 2700/3000<br>3500/4000/5000 | 840                 | 90  | 50000            | 45.6           | \$1.32                    |
| 24 61339                           | 11                  | 60                     | Brushed Nickel | Multi 5           | 2700/3000<br>3500/4000/5000 | 840                 | 90  | 50000            | 45.6           | \$1.32                    |
| <b>7.5 INCH LED SURFACE MOUNTS</b> |                     |                        |                |                   |                             |                     |     |                  |                |                           |
| 24 61340                           | 16                  | 75                     | White          | Multi 5           | 2700/3000<br>3500/4000/5000 | 1200                | 90  | 50000            | 45.6           | \$1.93                    |
| 24 61341                           | 16                  | 75                     | Black-Bronze   | Multi 5           | 2700/3000<br>3500/4000/5000 | 1200                | 90  | 50000            | 45.6           | \$1.93                    |
| 24 61342                           | 16                  | 75                     | Brushed Nickel | Multi 5           | 2700/3000<br>3500/4000/5000 | 1200                | 90  | 50000            | 45.6           | \$1.93                    |
| 24 61343                           | 16                  | 75                     | Chrome         | Multi 5           | 2700/3000<br>3500/4000/5000 | 1200                | 90  | 50000            | 45.6           | \$1.93                    |

\*Based on 3 hrs./day

\*\*Based on 3 hrs./day 11¢/kWh

24 Can be used to comply with the 2022 Title 24, part 6, high efficacy light source requirements.

## YouTube Videos



### Visit Our YouTube Channel for LED Educational Videos

In just a few minutes, learn more about these LEDs by watching our brief videos, visit <https://www.youtube.com/@westinghouselighting>



#### Long Life LED vs Incandescent Informational Video

 Learn more about the benefits of long-lasting LED technology.



#### Light Bulb Color Temperature Informational Video

 Discover how choosing the right color temperature can alter the ambiance of a room.



#### HID to High Lumen LED Conversion Video

 This informative tutorial includes the conversion of a parking lot light from a metal halide HID to an energy-efficient high lumen LED lamp.



#### TLED General Informational Video

 General information about Westinghouse TLED linear direct install and ballast bypass lamps.



#### TLED Single Ended Retrofit Informational Video

 Overview of our single-ended TLED lamps.



#### TLED Double Ended Retrofit Informational Video

 Overview of our double-ended TLED lamps.



#### 4 Ft. T8 LED Direct Install Installation Video

 Westinghouse T8 Direct Install LEDs can easily replace traditional fluorescent T8 lamps.



#### 4 Ft. T8 LED Ballast Bypass Installation Video

 T8 Ballast Bypass LEDs can replace traditional fluorescent T8 lamps but installation requires knowledge of fluorescent lighting fixtures and electrical systems.



#### 8 Ft. TLED FAQs Video

 We answer some of your most frequently asked questions about our 8 Ft. TLEDs.



#### 8 Ft. T8 LED Ballast Bypass Installation Video

 General overview of a ballast bypass installation for use with Westinghouse ballast bypass 8 ft T8 LEDs.



#### Universal TLED Informational Video

 Short overview of Linear TLED Universal lamps that operate on both single-ended and double-ended wiring.



#### Round Slim Recessed LED Downlight Installation Video

 Our slim recessed LEDs are even easier to install with the help of this video.



#### Square Recessed LED Downlight Installation Video

 Make installation of our standard LED downlights even easier with the help of this video.



#### Round Recessed LED Downlight Installation Video

 Make installation of our standard LED downlights even easier with the help of this video.

©2023 Google Inc. All rights reserved. YouTube is a trademark of Google Inc.



## WESTINGHOUSE LIGHTING

For additional information or to place your order call us at 800-999-2226, or contact your Westinghouse Lighting Sales Representative.

 and Westinghouse are trademarks of Westinghouse Electric Corporation. Used under license by Westinghouse Lighting. All Rights Reserved.